

# KÄRCHER

makes a difference



## CUSTOMIZED MOBILE CLEANING

An customizable pressure washer trailer for on-site cleaning.

# TRK-6000, TRK-3500



**TRK-6000** - shown with options and gas-powered hot water pressure washer; accommodates both gas and diesel-powered pressure washers.

## 1 Smart features

- Electrical wiring is recessed within the tubular frame.
- Lighted license plate holder and recessed tail lights.
- Two 3-way ball valves for easy switching of the water flow from the holding tank to a faucet.
- Electric brakes and break away kit

## 2 Outstanding mobility

- 1,500 lb.-rated swivel jack with a 2-5/16-inch ball coupler for quick and easy hook up of the trailer.
- Wheel and axle assembly has an industrial undercarriage leaf-spring suspension of up to 3,500 lbs. per axle and 15-inch, white-spoke wheels (TRK-6000 above shown with optional chrome wheels and fenders).

## Customizable mobile solution.

Kärcher has made customizing a mobile wash system for on-site cleaning as easy as 1-2-3:

- 1:** Choose from 3 rugged trailers—the dual-axle TRK-6000 with 330-gallon water tank or the single-axle TRK-3500 or TRK-2500 with 200-gallon water tank.
- 2:** Choose a compatible skid-mounted hot water pressure washer.
- 3:** Customize your trailer with a broad selection of options and accessories, such as hose reels, chrome coverings, etc.

## 3 Powerful and durable

- Extra-rugged 2-by-3 inch structural tubing is covered with a powder-coated epoxy black finish for all-weather protection.
- Durable steel cage for holding the tank and pressure washer in place.
- High-density, polyethylene water tank with 12-inch access port, 1-1/2-inch drain valve, 3/4-inch float valve and a 50-mesh inlet filter; two 5/16-inch chains for additional safety.

# Technical data and equipment

## Features

- Electrical wiring recessed within tubular frame
- Lighted license plate holder and recessed tail lights
- 1,000 lb. swivel jack with a 2-5/16-inch ball coupler for quick and easy hook up of the trailer.
- Two 3-way ball valves for easy switching of the water flow from the holding tank to a faucet
- Rugged steel cage for security while transporting.
- High-density, polyethylene water tank with a 12-inch access port, 1-1/2-inch drain valve, 3/4-inch float valve and a 50-mesh inlet filter; and two 5/16-inch chains for additional safety.
- Electric brakes and break away kit

## Technical Data

Model	Part No.	Axle	(GVWR) lbs.	Water tank (gallons)	Ship weight (lbs.)*
TRK-6000	1.103-807.0	Tandem	6000	330	1980
TRK-3500	1.103-806.0	Single	3500	200	840

\*trailer and water tank only



**TRK-3500** - shown with options; accommodates gasoline-powered pressure washers only.

## Optional Accessories

Order No.	Description	Order No.	Description
8.904-051.0	Battery installed on pressure washer	8.915-156.0	High-pressure hose, 3/8-inch x 100 ft., 2-Wire, installed
8.902-436.0	3" Lunette eye hitch coupler (TRK-3500)	8.902-447.0	Hose reel kit for 100 ft. Of 3/8-inch high-pressure hose
8.902-438.0	Hydraulic brakes, two axles, 2-5/16" ball coupler (TRK-6000)	8.902-448.0	Hose reel kit for 200 ft. Of 3/8-inch high-pressure hose
8.902-441.0	Hydraulic brakes, single axle, 2" ball coupler (TRK-3500)	8.902-449.0	Hose reel kit for 75 ft. Of 3/4-inch industrial garden hose
8.902-452.0	Hydraulic brakes, two axles, 3" Lunette eye coupler (TRK-6000)	8.902-455.0	Skid mounting & plumbing kit (required for mounting pressure washer to trailer)
8.924-493.0	From 2" to 2-5/16" ball hitch coupler (TRK-3500)	8.902-469.0	Sign plate
8.924-475.0	From 2-5/16" to 2" ball hitch coupler (TRK-6000)	8.902-466.0	Chrome wheels, pair, (2 pair required for trk-6000)
8.902-471.0	Electric Brakes - 3" Lunette eye hitch coupler (TRK-6000)	8.902-468.0	Chrome fenders, pair, trk-6000 tandem axle
8.902-442.0	Hydraulic Brakes Kit (Single axle, 3" Lunette eye hitch) (TRK-3500)	8.902-467.0	Chrome fenders, pair, trk-3500 single axle
8.912-409.0	2-5 gallon bucket chemical rack for TRK-6000 only (factory installed only)		