

KÄRCHER

makes a difference



HEAVY-DUTY HOT WATER CLEANING.

Hot water pressure washer with hand truck design.

HDS HAND TRUCK



Heavy-duty output.

Kärcher offers four North American designed models with their unique hand truck design, all-metal frame and heavy-duty vertical heating coil with stainless steel wrap. Units come with belt-drive Kärcher crankcase pumps. All are ETL certified to UL and CSA safety standards.



1 Powerful and Durable

- Industrial-grade motor with two-year warranty.
- High-output burner with transformer for years of reliable and affordable operation.
- Industrial-grade, tri-plunger, oil-bath, Kärcher pump with 7-year warranty.
- Heavy-gauge 11/4" steel frame with powder coat finish for all-weather protection.
- Insulated Schedule 80 heating coil is made of 1/2-inch steel pipe and cold-rolled; comes standard with stainless steel coil wrap and 5-year warranty.

2 Smart Features

- Cast iron pulley system with OSHA-compliant, totally enclosed belt guard, and easy-to-adjust belt tension (belt-drive models).
- Water resistant control box with burner on/off switch and adjustable thermostat.
- 50 ft. of wire braided hose with burst guard for added protection.
- High pressure rupture disc rated to 7000 lbs to protect user against injury.
- Options are auto start/stop or time delay shutdown, float tank, steam combination.
- EASY!Force trigger gun with cruise control like technology uses its own recoil force to hold the trigger down - so, no more sore hands after hours of use.

Technical data and equipment.

Technical Data

Model	Part No.	GPM	PSI	Drive	HP	Electrical	Amps	Pump	Weight (lbs.)	Dimensions (L x W x H) inches
HDS 3.9/20 Ea	1.575-505.0	3.9	2000	Belt	6	230V / 1ph	29	Kärcher KM	660	49 x 40 x 50
HDS 3.5/30 Ea	1.575-508.0	3.5	3000	Belt	7.5	230V / 1ph	36	Kärcher KM	690	49 x 40 x 50
HDS 3.5/30 Eb	1.575-509.0	3.5	3000	Belt	7.5	230V / 3ph	25	Kärcher KM	605	49 x 40 x 50
HDS 3.5/30 Ec	1.575-510.0	3.5	3000	Belt	7.5	460V / 3ph	13	Kärcher KM	605	49 x 40 x 50

Standard EASY!Force Accessory

Order No.	Description
8.756-481.0	EASY!Force trigger gun (North American Model) - zero force required. Standard 1/4" connection for wand, 3/8" connection for hose.

Options (factory installed)

Order No.	Description
9.801-008.0	Float tank (6-7.5 HP units, with soap valve)
9.801-006.0	Auto start/stop (6-7.5 HP models)
9.804-512.0	Auto start/stop and steam combo (6-7.5 HP models)
9.804-513.0	Auto start/stop and float tank (6-7.5 HP models)
9.804-514.0	Auto start/stop, steam and float tank (6-7.5 HP models)
9.804-515.0	Steam combination (6-7 HP, with float tank)
9.801-009.0	Steam combination (6-7 HP, without float tank)
9.801-001.0	Time delay

Time delay shutdown and auto start/stop are mutually exclusive

Options (field installed)

Order No.	Description
4.775-529.0	Extended Soft-grip Trigger Gun, ID 6, Integrated AVS hose connection
8.739-132.0	Kärcher Tuff-Flex, 1-wire, 3/8" ID, 100', 3000 PSI, 275°
9.801-023.0	100' EZEE hose reel kit (hose not included)